



The food and drug and fresh storage transport laboratory Tem

Model: **APEX-LJ355**

Standard: **JJF 1101-2003**

Introduce: ☆Introduction: APEX-LJ355 Temperature recorder is a series of higher cost temperature logger, have a reliable, simple operation, low power consumption...

Detailed product information

☆Introduction:

APEX-LJ355 Temperature recorder is a series of higher cost temperature logger, have a reliable, simple operation, low power consumption, the data is not lost after power failure, the waterproof performance is good, the LCD screen displays the status and temperature data data processing software and friendly interface.

☆Features:

- 1.APEX-LJ355 Temperature recorder can be set to attribute data recorder, including user information, instrument station number, the lower limit alarm parameters; work status indicators;
- 2.The instrument has stable performance, small size, large amount of information recorded, high precision, low power consumption.
3. One-button operation, LCD display indicates the working state, boot record, you can choose to stop recording;
- 4.Meet the HACCP requirements; temperature sensor can be built as well as external (factory configured for external sensors).

5.Power table shows the color battery capacity

Blue: 25% to 100%

Yellow: 10% to 25%

Red: <10% (proposed to replace the battery)

☆Main Specification

| | |
|--|---|
| power supply | 2.4Ah 3.6V non-rechargeable battery one (when the effective connection of the temperature recorder and computer, its power by the computer through the USB interface, supply) |
| the external conditions of temperature range | sensor: -40.0 °C ~ 70.0 °C |
| Sensor built-in conditions | -30.0 °C ~ 50.0 °C |
| the accuracy of temperature | -20 °C ~ 20 °C when ± 0.5 °C; remaining within ± 1 °C |
| Temperature Resolution | 0.1 °C |
| the cycle of records | 2 seconds to 24 hours continuous setting, or long according to the record by the recorder automatically assigned |
| sensor types | NTC |
| real-time transmission interval | 10-24 seconds adjustable |
| the recording capacity | RC-30: 3900 points; RC-30A: 8000; RC-30B: 16 000 points, product price is the RC-30, A, plus 50 yuan, B, plus 100 yuan. |
| Work environment | Temperature -30 °C ~ 50 °C, humidity 15% to 85% |
| data output and Protection class | via USB to computer exchange of data; IP65 |