



## multifunctional food safety detector

Price:

Model: **APEX-CJ556**

Standard:

Introduce: APEX-CJ556

multifunctional food safety detector Usage Has a full-color LCD touch screen operator interface is more user-friendly, simple, classic metal shell, elegant appearance, durable instrument built-in microcomputer, has 99 standard curve space, and can choose to use. Determination of the parameters menu selection, simple and convenient to use.

### Detailed product information

#### APEX-CJ556 multifunctional food safety detector Usage

Has a full-color LCD touch screen operator interface is more user-friendly, simple, classic metal shell, elegant appearance, durable instrument built-in microcomputer, has 99 standard curve space, and can choose to use. Determination of the parameters menu selection, simple and convenient to use.

#### APEX-CJ556 multifunctional food safety detector Features

1. Use the latest national standards promulgated
2. Suitable for the quantitative determination of the laboratory or in the field of liquid samples and solid samples
3. detection time for 5-30 minutes
4. Color touch-screen display, man machine interactive Chinese operations, with a measurement set, record, save and statistical processing function
5. Use cold light, monochromatic light source, optical stability is excellent, not affected by the interference of the variety of light
6. Lamp life up to 100,000 hours
7. Click the test items, the optical path to automatically switch to the appropriate measurement mode, convenient
8. Memory 99 standard curve can own revised and save
9. Memory regression fitting curve can be calculated and saved automatically. No need for manual production curve
10. Accurately storing 30,000 measurements data (including determination of time, parameter values)

#### APEX-CJ556 multifunctional food safety detector Parameters

Light source:	super bright light-emitting diodes
Wavelength:	380/420/460/510/560/610/700nm
Wavelength accuracy:	± 2nm
Photometric range:	0.000 ~ 2.000Abs
Stability:	0.005Abs / h
Curve Quantity:	99
Data storage:	30000
Detector:	integrated photoelectric sensor
Sample chamber:	cuvette than color tube
Display:	7-inch color touch screen
Operating environment:	5 ~ 40 °C
Measurement accuracy:	≤ ± 5%
Response time:	0.3 seconds

#### Friendly Tips:

We guarantee the product description is true and effective. After installation, for your safety, please use the instruments grounding. In the first year of your using the product, we replace the damaged parts. (Except consumables)

With decades of experience, we can provide a wide range of professional laboratory solutions. Please contact us if you can not find your desired lab equipment on our website. We will help you to find manufacturers who can guarantee the quality.